

GE

Energy Connections

Model 475I

Voltage Transformer
IEC Rated 50 Hz

Application

50 Hz.

Standard Secondary Voltage

110 Volts.

Insulation Level

0.72 kV

Accuracy Class:

0.2 @ 10VA.

0.5 @ 20VA.

Thermal Rating:

225VA at 30 °C. amb., 150VA at 55 °C. amb.

Primary and secondary terminals are ASA 8-32 brass screws with one flatwasher and lockwasher.

Approximate weight 5.7 kg



Clear Plastic Cover



Model 475I


Not fused	Catalog Number		Voltage Rating	Turns Ratio	Rec. Primary Fuse rating
	Primary Fuses Only	Primary and Secondary Fuses			
475I-110	475I-110F	475I-110FF	110:110	1:1	4 amp.
475I-220	475I-220F	475I-220FF	220:110	2:1	3 amp.
475I-380	475I-380F	475I-380FF	380:110	3.45:1	2 amp.
475I-400	475I-400F	475I-400FF	400:110	3.64:1	2 amp.
475I-416	475I-416F	475I-416FF	416:110	3.78:1	2 amp.
475I-440	475I-440F	475I-440FF	440:110	4:1	2 amp.

Above part numbers are available with 100 volt secondaries.



Model 475I

- The core and coil assembly is encased in a thermoplastic shell and filled with resin.
- These transformers are designed for operation line-to-line. They may also be operated line-to-ground or line-to-neutral at reduced voltage, (58% of rated volts).
- It is desirable to use a 3.0 amp BBS type or equal fuse in the secondary to protect the transformer.
- Transformer has a plastic terminal cover.



GEGridSolutions.com

Grid-AIS-L4-ITL_Model_475I-1150-2017_05-EN. General Electric Company and Instrument Transformers LLC reserve the right to change specifications of described products at any time without notice and without obligation to notify any person of such changes.

Worldwide Contact Center

Web: www.GEGridSolutions.com/contact

Phone: +44 (0) 1785 250 070

USA and Canada: +1 (0) 800 547 8629

Europe, Middle East and Africa: +34 (0) 94 485 88 00

