

Model CTM-0-2

**Double Bar Indoor Current Transformer
600 V, 10 kV BIL, 50-1,200 A Wound Primary**

Application

Designed for indoor service.
Suitable for operating meters, relays and control devices

Weight

(approximate)9 lbs

Reference Drawings

Outlines

50-400 A0121C42883


500-1,200 A0121C42884

Insulation Level

0.6 kV; BIL 10 kV full wave

Frequency

60 Hz



3 Wire Double Bar

Model CTM-0 - Double Bar

| Current Ratio (Amps) Pri : Sec | IEEE Accuracy Class, 60 Hz Burden Per IEEE | Continuous Thermal Current Rating Factor | Approval Number from CCAC | Catalog Number |
|--------------------------------------|---|---|------------------------------|----------------|
| | B0.1 to B0.2 | @ 30 °C Amb. | | |
| 50/50:5 | 0.3 | 1.5 | T-156 | 440-001 |
| 100/100:5 | 0.3 | 1.5 | T-156 | 440-002 |
| 150/150:5 | 0.3 | 1.5 | T-156 | 440-003 |
| 200/200:5 | 0.3 | 1.5 | T-156 | 440-004 |
| 300/300:5 | 0.3 | 1.5 | T-156 | 440-005 |
| 400/400:5 | 0.3 | 1.5 | T-156 | 440-006 |
| 500/500:5 | 0.3 | 1.5 | T-286 | 440-007 |
| 600/600:5 | 0.3 | 1.5 | T-286 | 440-008 |
| 800/800:5 | 0.3 | 1.5 | T-286 | 440-009 |
| 1,000/1,000:5* | 0.3 | 1.2 | T-286 | 440-010 |
| 1,200/1,200:5* | 0.3 | 1.0 | T-286 | 440-011 |

* For these models please contact factory for availability and approval number from CCAC for revenue metering application.



Model CTM-0

Construction and Insulation

The core and coil are encapsulated in polyurethane resin within a molded case. This material has excellent electrical and mechanical properties over a wide temperature range, has very low water absorption and is resistant to oil and a variety of chemicals.

Core and Coils

The core is made from high quality grain oriented silicon steel, annealed under rigidly controlled factory conditions. The secondary winding is made of heavy enameled copper wire. The secondary windings are evenly distributed around the core for maximum accuracy and resistance to stray fields from adjacent conductors.

Terminals

Secondary terminals are tin plated brass, compression type. A shorting device is provided and interlocked to the terminal cover in such a way as to prevent connection error. The terminal cover is made of a clear plastic. Provision is made for sealing the cover.

Primary Bars

The primary terminals are tin plated copper bars.

Polarity


Primary and secondary polarity marks H1, H2 and X1, X2 are molded into the case.

Nameplate


The nameplate is laser engraved aluminum. The nominal current rating of the transformer is marked on the side in large numerals.

Maintenance



These transformers require no maintenance, other than occasional cleaning, if installed where air contamination is severe.



Current Ratio from 50/50:5 to 400/400:5



Current Ratio from 500/500:5 to 1200/1200:5



GEGridSolutions.com

ITI-Model-CTM-0-2-Spec-EN-2020-12-Grid-AIS-1374. © Copyright 2020. General Electric Company and Instrument Transformers LLC reserve the right to change specifications of described products at any time without notice and without obligation to notify any person of such changes.

Worldwide Contact Center

Web: www.GEGridSolutions.com/contact

Phone: +44 (0) 1785 250 070

USA and Canada: +1 (0) 800 547 8629

Europe, Middle East and Africa: +34 (0) 94 485 88 00